

## Tank rental fleet

REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



### Dimensions and Weights

1,5 m3 tank	Size (L*W*H)	Contents	Tare weight	Max. Payload	M.G.W.	Max. pressure
1,5 m3 S	1372*1372*2189	1500L	1100kg	3000kg	4100kg	4 bar

2,3 m3 – 3 m3 tank	Size (L*W*H)	Contents	Tare weight	Max. Payload	M.G.W.	Max. pressure
2,3 m3 S	2150*1900*2200	2300L	1900kg	3850kg	5750kg	4 bar
2,5 m3	1795*1795*2315	2500L	1670kg	4830kg	6500kg	4 bar
2,5 m3	1795*1795*2315	2500L	1800kg	4700kg	6500kg	4 bar
2,7 m3 S	2150*1900*2350	2700L	2140kg	3860kg	6000kg	4 bar
2,7 m3 S	2000*2000*2235	2700L	1790kg	4710kg	6500kg	4 bar
2,9 m3	1920*1920*2390	2900L	1700kg	3300kg	5000kg	4 bar
3 m3	1920*1920*2390	3000L	1700kg	3300kg	5000kg	4 bar

3,8 m3 - 4 m3 tank	Size (L*W*H)	Contents	Tare weight	Max. Payload	M.G.W.	Max. pressure
3,8 m3	1998*1998*2520	3800L	1651kg	5849kg	7500kg	4 bar
4 m3	2200*2200*2610	4000L	1970kg	6030kg	8000kg	4 bar

If you would like more information, please contact one of the REYM branches in your region.

[info@reym.nl](mailto:info@reym.nl) // [www.reym.nl](http://www.reym.nl)

4,2 m3 - 5 m3 tank	Size (L*W*H)	Contents	Tare weight	Max. Payload	M.G.W.	Max. pressure
4,2 m3	1995*1989*2530	4200L	1970kg	6030kg	8000kg	4 bar
4,5 m3 S	2750*1850*2470	4500L	2400kg	8100kg	10500kg	4 bar
4,5 m3 Com- pact S	2300*2300*1945	4500L	2500kg	8100kg	10600kg	4 bar
4,8 m3	2200*2200*2610	4800L	2500kg	9500kg	12000kg	4 bar
4,8 m3 vac.	2200*2200*2610	4800L	3200kg	6800kg	10000kg	-0,9 / 4 bar
4,8 m3 vac.	2200*2200*2610	4800L	2500kg	9500kg	12000kg	-0,9 / 4 bar
5 m3	2300*2300*2560	5000L	2450kg	7550kg	10000kg	4 bar

7,6 m3 - 8,4 m3 tank	Size (L*W*H)	Contents	Tare weight	Max. Payload	M.G.W.	Max. pressure
7,6 m3	2991*2438*2591	7570L	3150kg	7350kg	10500kg	4 bar
7,6 m3	2991*2438*2591	7570L	2300kg	10700kg	13000kg	4 bar
8 m3	2991*2438*2591	8000L	3000kg	12000kg	15000kg	2,67 bar
8,2 m3 vac.	2991*2438*2591	8200L	3350kg	11650kg	15000kg	-0,9 / 4 bar
8,2 m3	2991*2438*2591	8200L	3350KG	11650kg	15000kg	4 bar
8,4 m3	2991*2438*2591	8400L	3490kg	21510kg	25000kg	4 bar

20 m3 tank	Size (L*W*H)	Contents	Tare weight	Max. Payload	M.G.W.	Max. pressure
20 m3 S	6000*2442*2600	20000L	6000kg	19000kg	25000kg	2,67 bar
20 m3	6058*2438*2667	20000L	5050kg	19950kg	25000kg	2,67 bar

All tanks are designed and manufactured according EN 12079-1 & DNV 2.7-1. Periodic examined according EN 10855-3.  
And all slings and lifting accessories are designed and manufactured according EN 12079-2. Periodic examined according EN 10855-3.

If you would like more information, please contact one of the REYM branches in your region.

info@reym.nl // www.reym.nl