

REYMtainer

REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



Clients regularly request the supply of temporary storage facilities for (fluid) materials. REYM has an extensive range of storage containers and tanks to meet this demand. Due to the increasing demand, REYM now also has a number of mobile storage tanks at its disposal.

The new storage tanks are called REYMtainers. These are trailers with a tank capacity of no less than 85 m³, which is almost three times as much as a normal tank trailer.

The REYMtainers are built within the maximum transport dimensions, so no special transport needs to be arranged.

By applying a special coating inside of the tank, they are suitable for the storage of the most common substances.

For transport on public roads, the tank is equipped with a lifting rear axle, which can be brought into position by means of two pneumatically operated air springs. Of course, the

tanks are equipped with all the necessary safety equipment, because working safely at REYM is the top priority.

For example, the roof of the tank is fitted with railing around it. The safety when operating the connections located there is thus guaranteed. Immediately behind the rear axle there are two material boxes and a carriage in which a drip tray can be stored. The REYMtainer has a level detector to prevent overfilling.

During the development of the REYMtainer, the safety of other road users was taken into account. Both sides of the tank are fitted with safety plates to protect cyclists and other road users. The tank is equipped with all the prescribed lighting and reflective materials.

The rental of the REYMtainers is taken care of from all our branches. For further information, please contact the head office on 033 455 88 90.

Some technical data of the REYMtainer

Dimensions REYMtainer

- Length: 13.000 mm
- Width: 2540 mm
- Height: 3960 mm

Weights and capacity

- Total weight ready for use: 14.480 kg
- Max permissible weight: 22.000 kg
- Max. permissible weight on king pin: 13.000 kg
- Max. permissible weight on rear axle: 10.000 kg
- Tank capacity: 86.000 liter
- Max permissible specific gravity load: 1300 kg/m³

Pressure and temperature

- Pressure relief valve is set to: 69 mbar overpressure
69 mbar overpressure
- 1.7 mbar vacuum
- Max temperature of stored substance: 50 degrees
Celsius

Coating

- Exterior: 2-component polyester-based lacquering
system
- Interior: Epoxy-phenol coating, resistant to chemicals
and hydrocarbons.

Further information on resistance to certain chemicals
is available on request.

If you would like more
information, please contact
one of the REYM branches
in your region.

info@reym.nl // www.reym.nl