

REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



IBC CARRIER DNV 2.7-1

Specification

Material	Carbon steel galvanized
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 1.700 mm x W 1.500 mm x L 1.500 mm
Lift fork pockets	Yes
Tare weight	950 KG
Payload	2.050 KG
Max. gross weight	3.000 KG
Approvals & Certification	DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines

All specifications are indicative. Individual dimensions may differ.

If you would like more information, please contact our REYM branche in Beverwijk.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



7M³ MUD SKIP DNV 2.7-1

Specification

Material	Carbon Stainless Steel Galvanized
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 1.660 mm x W 1.820 mm x L 3.580 mm
Lift fork pockets	Yes
Capacity	7.000 L
Tare weight	1.900 KG
Payload	10.000 KG
Max. gross weight	11.900 KG
Approvals & Certification	DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Options	Lid.

If you would like more information, please contact our REYM branche in Beverwijk.

offshore@reym.nl // www.reym.nl

All specifications are indicative. Individual dimensions may differ.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



1.500 L TANK

OFFSHORE TANK DNV 2.7-1

Specification

Material	316L stainless Steel
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 1.365 mm x W 1.365 mm x L 2.210 mm
Lift fork pockets	yes
Capacity	1.500 L
Tare weight	1.100 KG
Payload	3.000 KG
Max. gross weight	4.100 KG
Working pressure	4 Bar
Approvals & Certification	T7 / T11 UN portable tank
	DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Mechanical data specification	Inlet connection - 2" BSP
	Outlet connection - 2" BSP
	Valve - yes
	Ventline - yes
Options	Anode, x-over couplings

If you would like more information, please contact our REYM branche in Beverwijk.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



3.800L - 5.000L TANK

OFFSHORE TANK DNV 2.7-1

Specification

Material	316L stainless Steel
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 2.760 mm x W 1.850 mm x L 2.310 mm
Lift fork pockets	Yes
Capacity	5.000 L
Tare weight	2.450 KG
Payload	7.550 KG
Max. gross weight	10.000 KG
Working pressure	4 Bar
Approvals & Certification	T7 / T11 UN portable tank DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Mechanical data specification	Inlet connection - 2" BSP Outlet connection - 2" BSP Valve - yes Ventline - yes
Options	Level gauge, Anode, x-over couplings

If you would like more information, please contact our REYM branche in Beverwijk.

offshore@reym.nl // www.reym.nl

All specifications are indicative. Individual dimensions may differ.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



4.800L TANK (T14 TOP DISCHARGER FOR NORM WASTE)

OFFSHORE TANK DNV 2.7-1

Specification

Material	316L stainless Steel
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 2.345 mm x W 2.438 mm x L 2.438 mm
Lift fork pockets	Yes
Capacity	4.800 L
Tare weight	3.200 KG
Payload	6.800 KG
Max. gross weight	10.000 KG
Working pressure	4 Bar
Approvals & Certification	T14 UN portable tank DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Mechanical data specification	Inlet connection - Top Outlet connection - Top Valve - no Ventline - yes
Options	Handrail, Anode, x-over couplings

If you would like more information, please contact our REYM branche in Beverwijk.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



2.300L - 3.000L TANK OFFSHORE TANK DNV 2.7-1

Specification

Material	316L stainless Steel
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 1.920 mm x W 1.920 mm x L 2.420 mm
Lift fork pockets	Yes
Capacity	316 L
Tare weight	2.330 KG
Payload	8.100 KG
Max. gross weight	10.430 KG
Working pressure	4 Bar
Approvals & Certification	T7 / T11 UN portable tank DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Mechanical data specification	Inlet connection - 2"BSP Outlet connection - 2"BSP Valve - yes Ventline - yes
Options	Level gauge, Anode, x-over couplings

If you would like more information, please contact our REYM branche in Beverwijk.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



7.600L – 8.000L TANK OFFSHORE TANK DNV 2.7-1

Specification

Material	316L stainless Steel
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 2.980 mm x W 2.430 mm x L 2.600 mm
Lift fork pockets	Yes
Capacity	8.200 L
Tare weight	3.350 KG
Payload	11.650 KG
Max. gross weight	15.000 KG
Working pressure	4 Bar
Approvals & Certification	T7 / T11 UN portable tank DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Mechanical data specification	Inlet connection - 3" BSP Outlet connection - 3" BSP Valve - yes Ventline - yes

If you would like more information, please contact our REYM branche in Beverwijk.



REYM is an industrial service provider. We support our customers in the field of industrial cleaning, transport and waste management, always acting from our mission 'Industrial Services our concern' and driven by our core values.



20.000L TANK

OFFSHORE TANK DNV 2.7-1

Specification

Material	316L stainless Steel
Slings	Units will be supplied with DNV certified slings
External nominal dimensions	H 2.700 mm x W 2.420 mm x L 6.080 mm
Lift fork pockets	Yes
Capacity	20.000 L
Tare weight	5.400 KG
Payload	19.600 KG
Max. gross weight	25.000 KG
Working pressure	2,67 Bar
Approvals & Certification	T7 / T11 UN portable tank DNV 2.7-1, IMO, IMDG, ADR, EN12079, Nogepa guidelines
Mechanical data specification	Inlet connection - 3"-4" BSP + NPT Outlet connection - 3"-4" BSP + NPT Valve - yes Ventline - yes
Options	Level gauge, Anode, x-over couplings

If you would like more information, please contact our REYM branche in Beverwijk.